

# RM-PT

AUTONOMOUS MOBILE ROBOT



*robomate*

RM-PT-15

## RM-PT



1500kg Payload



Ergonomic Design



Support open pallet type



### BASIC INFORMATION

Base Dimension	Length: 1513 mm
	Width: 791 mm
	Height: 1875 mm

Ground Clearance	20 mm
------------------	-------

Carry Payload	1500 kg
---------------	---------

Lifting Height	210 mm
----------------	--------

### PERFORMANCE

Maximum Speed	1 m/s ( 3.6 km/h)
---------------	-------------------

Stopping Accuracy	$\pm 100$ mm $\pm 2^\circ$
-------------------	----------------------------

Lifting Speed	0.04 m/s
---------------	----------

Maximum Gradeability	3% / 1.72°
----------------------	------------

### DRIVING & NAVIGATION

Navigation System	Laser-based Natural Feature
-------------------	-----------------------------

Turning Radius	1290 mm
----------------	---------

## SAFETY

---

Protective Devices	Emergency Switch, Physical Bumper, Safety Laser
--------------------	---

---

Indicator	Speakers, LED Lighting, Lighting Beacon
-----------	---

## POWER

---

Running Time	6 ~ 8 hours
--------------	-------------

---

Charging Method	Auto Charge: Dock charging through charging station Manual Charge: Through cable
-----------------	---

---

Battery	48 V / 60 AH LiFePO4
---------	----------------------

## INTERFACE

---

Language	English
----------	---------

---

Operating System	NavWiz
------------------	--------

---

Screen	7" , Capacitive touchscreen
--------	-----------------------------

---

Communications	802.11 a/b/g/n, 2.4GHz / 5GHz WiFi, Open WiFi, WPA & WPA2 Personal, WPA & WPA2 Enterprise
----------------	---

RM-PT-15

# RM-PT

